

LED T8 Tube lamp 2ft in Frosted PC



Model No.	MS-TB2606
Input Voltage(VAC)	AC100-277V
Frequency Range(HZ)	50-60Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion	<15%
Power Efficiency	85%
Working Voltage(VDC)	DC34-38
LED Luminous Efficiency	>80lm/watt
LED Consumption(W)	6.6W
System Consumption(W)	8W
LED Initial Flux(LM)	>640lm
Lamp's Efficiency(%)	90%
Color Temperature	6500K(PW), 3000K(WW), 4100K(NW),
Color Rendering Index(CRI)	Ra>75
Junction Temperature	85 °C 185F
Working Enviornment	<90% humidity
IP Rating	IP54
Working Life	35,000-50,000 hours
Tube Lamp material	PC + Aluminum
Net Weight	0.44lb 0.2kgs
Packing Size(mm)	620 x 34 x 34
Certification	CE/LVD,CE/EMC,RoHs,UL





LED T8 Tube lamp 2ft in Clear PC

Model No.	MS-TB2606
Input Voltage(VAC)	AC100-277V
Frequency Range(HZ)	50-60Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion	<15%
Power Efficiency	85%
Working Voltage(VDC)	DC34-38
LED Luminous Efficiency	>90lm/watt
LED Consumption(W)	6.6W
System Consumption(W)	8W
LED Initial Flux(LM)	>720lm
Lamp's Efficiency(%)	90%
Color Temperature	6500K(PW), 3000K(WW), 4100K(NW),
Color Rendering Index(CRI)	Ra>75
Junction Temperature	85 °C 185F
Working Enviornment	<90% humidity
IP Rating	IP54
Working Life	35,000-50,000 hours
Tube Lamp material	PC + Aluminum
Net Weight	0.44lb 0.2kgs
Packing Size(mm)	620 x 34 x 34
Certification	CE/LVD,CE/EMC,RoHs,UL



LED T8 Tube lamp 3ft in Clear PC



Model No.	MS-TB2609
Input Voltage(VAC)	AC100-277V
Frequency Range(HZ)	50-60Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion	<15%
Power Efficiency	85%
Working Voltage(VDC)	DC34-38
LED Luminous Efficiency	>90lm/watt
LED Consumption(W)	11W
System Consumption(W)	13W
LED Initial Flux(LM)	>1200lm
Lamp's Efficiency(%)	90%
Color Temperature	6500K(PW), 3000K(WW), 4100K(NW),
Color Rendering Index(CRI)	Ra>75
Junction Temperature	85 °C 185F
Working Enviornment	<90% humidity
IP Rating	IP54
Working Life	35,000-50,000 hours
Tube Lamp material	PC + Aluminum
Net Weight	0.66lb 0.3kgs
Packing Size(mm)	620 x 34 x 34
Certification	CE/LVD,CE/EMC,RoHs,UL



LED T8 Tube lamp 3ft in Frosted PC



Model No.	MS-TB2609
Input Voltage(VAC)	AC100-277V
Frequency Range(HZ)	50-60Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion	<15%
Power Efficiency	85%
Working Voltage(VDC)	DC34-38
LED Luminous Efficiency	>80lm/watt
LED Consumption(W)	11W
System Consumption(W)	13W
LED Initial Flux(LM)	>1050lm
Lamp's Efficiency(%)	90%
Color Temperature	6500K(PW), 3000K(WW), 4100K(NW),
Color Rendering Index(CRI)	Ra>75
Junction Temperature	85 °C 185F
Working Environment	<90% humidity
IP Rating	IP54
Working Life	35,000-50,000 hours
Tube Lamp material	PC + Aluminum
Net Weight	0.66lb 0.3kgs
Packing Size(mm)	620 x 34 x 34
Certification	CE/LVD,CE/EMC,RoHs,UL



LED T8 Tube lamp 4ft in Clear PC



Model No.	MS-TB2612
Input Voltage(VAC)	AC100-277V
Frequency Range(HZ)	50-60Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion	<15%
Power Efficiency	85%
Working Voltage(VDC)	DC34-38
LED Luminous Efficiency	>90lm/watt
LED Consumption(W)	16W
System Consumption(W)	18.5W
LED Initial Flux(LM)	>1700lm
Lamp's Efficiency(%)	90%
Color Temperature	6500K(PW), 3000K(WW), 4100K(NW),
Color Rendering Index(CRI)	Ra>75
Junction Temperature	85 °C 185F
Working Enviornment	<90% humidity
IP Rating	IP54
Working Life	35,000-50,000 hours
Tube Lamp material	PC + Aluminum
Net Weight	0.88lb 0.4kgs
Packing Size(mm)	1235 x 34 x 34
Certification	CE/LVD,CE/EMC,RoHs,UL



LED T8 Tube lamp 4ft in Frosted PC



Model No.	MS-TB2612
Input Voltage(VAC)	AC100-277V
Frequency Range(HZ)	50-60Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion	<15%
Power Efficiency	85%
Working Voltage(VDC)	DC34-38
LED Luminous Efficiency	>80lm/watt
LED Consumption(W)	16W
System Consumption(W)	18.5W
LED Initial Flux(LM)	>1500lm
Lamp's Efficiency(%)	90%
Color Temperature	6500K(PW), 3000K(WW), 4100K(NW),
Color Rendering Index(CRI)	Ra>75
Junction Temperature	85 °C 185F
Working Enviornment	<90% humidity
IP Rating	IP54
Working Life	35,000-50,000 hours
Tube Lamp material	PC + Aluminum
Net Weight	0.88lb 0.4kgs
Packing Size(mm)	1235 x 34 x 34
Certification	CE/LVD,CE/EMC,RoHs,UL





LED T8 Tube lamp 5ft in Clear PC

Model No.	MS-TB2615
Input Voltage(VAC)	AC100-277V
Frequency Range(HZ)	50-60Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion	<15%
Power Efficiency	85%
Working Voltage(VDC)	DC34-38
LED Luminous Efficiency	>90lm/watt
LED Consumption(W)	18W
System Consumption(W)	21W
LED Initial Flux(LM)	>1890lm
Lamp's Efficiency(%)	90%
Color Temperature	6500K(PW), 3000K(WW), 4100K(NW),
Color Rendering Index(CRI)	Ra>75
Junction Temperature	85 °C 185F
Working Enviornment	<90% humidity
IP Rating	IP54
Working Life	35,000-50,000 hours
Tube Lamp material	PC + Aluminum
Net Weight	1.1lb 0.5kgs
Packing Size(mm)	1235 x 34 x 34
Certification	CE/LVD,CE/EMC,RoHs,UL





LED T8 Tube lamp 5ft in Frosted PC

Model No.	MS-TB2615
Input Voltage(VAC)	AC100-277V
Frequency Range(HZ)	50-60Hz
Power Factor(PF)	>0.9
Total Harmonic Distortion	<15%
Power Efficiency	85%
Working Voltage(VDC)	DC34-38
LED Luminous Efficiency	>80lm/watt
LED Consumption(W)	18W
System Consumption(W)	21W
LED Initial Flux(LM)	>1680lm
Lamp's Efficiency(%)	90%
Color Temperature	6500K(PW), 3000K(WW), 4100K(NW),
Color Rendering Index(CRI)	Ra>75
Junction Temperature	85 °C 185F
Working Enviornment	<90% humidity
IP Rating	IP54
Working Life	35,000-50,000 hours
Tube Lamp material	PC + Aluminum
Net Weight	1.1lb 0.5kgs
Packing Size(mm)	1235 x 34 x 34
Certification	CE/LVD,CE/EMC,RoHs,UL

